

Floor trunking 2m and 85x18mm with 2 compartments

REF. TF11172/8



BASIC INFORMATION

DESCRIPTION

The DCS TF11172/8 floor trunking, with an anodized aluminum cover, is an ideal solution for the distribution of electrical and data cabling indoors. Designed for floor installations, it offers a profile of 85x18 mm, making it perfect for spaces with high connectivity demands such as offices, workplaces, and educational centers. With IK08 mechanical resistance and a maximum load capacity of 45 kg/cm², it guarantees durability against impacts, foot traffic, and the occasional passage of vehicles. Its installation system allows for quick fixing with screws and easy maintenance thanks to the removal of the cover with specific tools.

FINISH

Aluminium

MATERIAL

Aluminium

ETIM CLASS

EC000722

TECHNICAL INFORMATION

IK CLASSIFICATION

08

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

45 Kg/cm²

MONOBLOCK

No

RAL

7035

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

REMOVAL OF THE FRAME

Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053229088

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436027978

PACKAGING VOLUME

16240500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

8

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

90

PACKAGING GROSS WEIGHT

6

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

90

PACKAGING NET WEIGHT

6

UNITARY PACKAGING GROSS
WEIGHT

0

PACKAGING LENGTH

2005

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.75