

Luminaire RS 20 9,4W 4000K with detector 8m HF+LUX IP44

REF. 89191100-094



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF sensor, power 9.4 W, luminous flux of 965 lm, and color temperature of 4000 K.

The maximum installation height is 4m, and the installation is surface-mounted. The detection range is 8m, and the detection angle is 360°.

The light regulation range is 2 - 2000 lux, and the timing range is 5 s - 15 min.

Allows the interconnection of master/master and master/slave luminaires.

The power supply voltage is 220 - 240 VAC. The operating temperature is: -10 - 40 °C.

Protection grade IP 54 and IK 3 and dimensions: Ø 272 x 64 mm.

5-year warranty.

For more product information, visit the STEINEL website by clicking [here](#).

FINISH

White

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

POWER SUPPLY (V~)

220/240 V~

IK CLASSIFICATION

03

OPERATING TEMPERATURE RANGE (°C)

-10...+40

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface mounting

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053431528

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.752

PRODUCT NET WEIGHT

0.437

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053431528

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

300

PACKAGING WIDTH

120

PACKAGING LENGTH

300

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.752

PACKAGING NET WEIGHT

0.437

PACKAGING WEIGHT UNIT

KGM