

Module for 1 Keystone II RJ45 AMP®, Brand Rex® or Simon® in angled voice and data plates

REF. MD67



BASIC INFORMATION

DESCRIPTION

This product consists of a module for 1 Keystone II RJ45 from AMP®, Brand Rex® or Simon® in angled voice and data belonging to the Simon 500 Cima series. The module is exclusively designed for plates of this range of type inclined, as the angled voice and data plates for Simon are included with the module. Its dimensions are 32 x 20 millimetres and 10 millimetres of depth, and its installation is very simple. The product is made of thermoplastic insulation. These components are of the highest quality, as well as all the used by Simon. Thanks to the product has a resistance and hardness extra that extends considerably its service life and allows you to operate even low temperatures ranging from -5 and 60 degrees centigrade. Added to all this is the capacity of the module extinguish the spread in case of fire management and reduces the toxicity in the flue gas in case of producing. Which contributes without a doubt to increase in a considerable the security of the end product.

COMPATIBILITY

Simon 500 Cima and Simon K45 angled voice and data plates

PACKAGING CONTENTS

MD Module for 1 RJ45

ETIM CLASS

EC002948

REMARKS

The MD Module can only be combined with angled voice and data plates (flat voice and data plates include the MD Module on the plate itself).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

COMPATIBLE WITH CONNECTORS

Simon®, AMP netconnect® Series Standard 110, SL110, SL Tool less, Brand-Rex®, Panduit® Series Netkey, Rit® and manufacturers of RJ45 with Keystone II snap-fit system.

RJ45 CONNECTORS

Not included in the MD Module

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

FORMAT

RJ45

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

SNAP-FIT RJ45 PLATES

RJ45 AMP®, Brand Rex® or Simon® connectors

SNAP-FIT TYPE

RJ45 AMP®, Brand Rex® or Simon® connectors

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Vertical, corresponding with the MD Module fastening slots

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.003

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

455000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436025394

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

50

PACKAGING GROSS WEIGHT

0.15

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

65

PACKAGING NET WEIGHT

0.15

UNITARY PACKAGING GROSS
WEIGHT

0.003

PACKAGING WIDTH

70

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

100