

PD-6x6 Micro PIR+LUX SR recessed On/Off black IP65

REF. 89219311-138



BASIC INFORMATION

DESCRIPTION

PIR presence and luminosity detector for flush mounting. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 90°. The tangential detection range is 6 x 6 m and the radial detection range is 4 x 4 m.

The luminosity regulation range is 2 - 1000 lux and the timing range is 5 s - 60 min. The configuration of the detector is done via remote control.

It has a TEACH operating mode. Possibility of interconnection between master/master and master/slave sensors up to 10 detectors. The control output is On/Off and the maximum switchable power is 1000 W (600 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -25 - 55 °C.

Black finish, IP 65 protection rating and dimensions: Ø 43 x 75 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Black

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

1000

RAL

9005

IP RATING

IP65

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053343159

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.3

PRODUCT NET WEIGHT

0.232

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053343159

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

92

PACKAGING WIDTH

76

PACKAGING LENGTH

125

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

874000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.3

PACKAGING NET WEIGHT

0.232

PACKAGING WEIGHT UNIT

KGM