

MD-23x6 Hallway PIR+LUX recessed On/Off round white IP20

REF. 89205115-130



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted motion and light detector. The recommended installation height is 2.8 m, with a maximum height of 5 m. It has a detection angle of 360° and an opening angle of 45°. The tangential detection range is 23 x 6 m and the radial detection range is 12 x 6 m. The luminosity regulation range is 2 - 2000 lux and the timing range is 5 s - 15 min. The configuration of the detector is carried out through potentiometers and remote control. It has a TEACH operating mode. Possibility of interconnection between master/master sensors up to 10 detectors. The control output is On/Off and the maximum switchable power is 2000 W (600 W LED). The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C. White finish, IP 20 protection rating, and dimensions: Ø 124 x 121 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH
White

**COMPATIBLE WITH MECHANICAL
PUSH BUTTON**
No

ETIM CLASS
EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053341841

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.249

PRODUCT NET WEIGHT

0.159

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053341841

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

141

PACKAGING WIDTH

141

PACKAGING LENGTH

141

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2803221

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.249

PACKAGING NET WEIGHT

0.159

PACKAGING WEIGHT UNIT

KGM