

Complete kit with cover, metal fin, 4 schuko socket outlets and plate for 2 RJ45 connectors white S400 Indesk

REF. 45504020-130



BASIC INFORMATION

DESCRIPTION

Simon has been providing electrical solutions for all types of spaces for over a century, effectively combining design, functionality, and quality. This is reflected in the Simon 400 Indesk series, to which this complete kit integrated into the table belongs, featuring a cover and fin, 4 schukos, and a plate for 2 RJ45 connectors in white. The extra resistance offered by the anodized aluminum profile and its enclosure in painted steel ensures that this product remains as good as new over the years. Simon also addresses unforeseen events by creating its covers and supports from a material that prevents flame propagation and the release of toxic gases in case of fire; this material is the self-extinguishing halogen-free thermoplastic. Designed for 250 volts and 16 amps, it measures 295 x 185 x 85 millimeters.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with metal fin

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

IK CLASSIFICATION

07

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

-5...+60

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9016

RECESS DIMENSION (MM)

273 x 175 mm (± 2mm)

NUMBER OF RJ45 WINDOWS

2

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

SNAP-FIT TYPE

Keystone I, II and Systimax

NUMBER OF SOCKETS

4 sockets for standard current circuit

VERSION

5 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With metal fin

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45°

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053208397

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053208397

PACKAGING VOLUME

5265000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

300

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

195

PACKAGING NET WEIGHT

2.15

UNITARY PACKAGING GROSS
WEIGHT

2.15

PACKAGING LENGTH

90

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

2.15