

French double socket outlet 16A 250V~ with safety device and screw terminal connection red Simon 500 Cima

REF. 50000458-037



BASIC INFORMATION

DESCRIPTION

Between the sockets and covers for electrical outlets Simon we find this double French socket outlet, current 16 A / 250V. has a safety device and the rocker operation is screwed. It is part of the Simon 500 Cima series and commitment to a stylish and vibrant finished in red colour. This socket outlet Simon can be installed on the surface-mounted or recessed. It has a total of two modules and withstands temperatures very extreme temperatures (-25 to + 60 degrees centigrade). In terms of the wire that supports is between 1.5 and 2.5 millimetres and the stripping of the need to wire is 12 millimetres. The dimensions of the exact French socket outlet Simon are 100 x 50 millimetres and a depth of 46 millimetres. It is made of metal components isolated thermoplastically and free of halogens. This type of materials eliminate the possibility of a flame spread and can reduce the toxicity in case of smoke.

FINISH

Red

PACKAGING CONTENTS

Double socket outlet with cover and installation manual

ETIM CLASS

EC000125

COMPATIBILITY

Simon 500 Cima enclosures

TECHNICAL INFORMATION

AVAILABLE MARKET CE	INSULATION RESISTANCE (V-MΩ) >5MΩhms at 500V	TYPE OF MECHANISM Insertion
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	CURRENT (A) 16 A	NUMBER OF MODULES 2
NUMBER OF CONNECTIONS PER TERMINAL 2 connections per terminal	IP RATING IP20	MONOBLOCK No
DIELECTRIC STRENGTH No holes or contours, with 2000V at 50 Hz for 1 minute	LINKABLE Yes, using accessory 50000996-039	NOMINAL VOLTAGE (V~) 250 V~
FORMAT French	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	RAL 3002
HEAT RESISTANCE (°C) +125°C (according rule IEC 60695-10-2)	TEMPERATURE RANGE DURING INSTALLATION (°C) -25 to 60 °C	NUMBER OF SOCKETS 2
INDICATOR FUNCTION No		VERSION Double

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 12	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Specific Simon 500 Cima	REMOVAL OF THE SOCKET Only with tool
REMOVAL OF COVER Only with tool	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw
EXTINGUISHING (°C) +850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)	INSTALLATION TYPE Suitable for surface and flush mounting	NUMBER OF TERMINALS 3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

1.07

PACKAGING WIDTH

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

0

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053112748

PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME

0

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

1.07

PACKAGING HEIGHT

0

PACKAGING NET WEIGHT

10.7

PACKAGING WEIGHT UNIT

KGM

