

Mini beacon kits 830.30 WW

REF. 83030042-883



BASIC INFORMATION

DESCRIPTION

The range of mini beacons of the brand Simon, have features that make it suitable to resolve the problems of lighting of linear definition. Suitable for signposting of steps, entrances and paths, allow a clear. Designed for perfect assembly in surface-mounted. Decorative, indirectas and auxiliary tasks in all linearity. Indoor lighting. Kit mini beacon 830.30 WW, Category A, warm colour temperature of 3100 K, translucent. 250 lm / 4,9W, 25,000 h at 25 ° C. with LED technology for installation Semi- flush-mounted. Manufactured and finished in stainless steel. Electronic control gear (power) included in the luminaire packaging (3 mini beacons per box), with ON-OFF control, insulated from the optical body and the heat emission, which ensures a longer service life. 250 lm lumens available for WW, and total luminaire consumption of 4,9W. (Actual system efficiency of 51 lm / w). CRI > 80. Dimensions luminaire: Diameter 45mm x 33,3 mm high. IP 20. Hole diameter: 38 mm Weight of the luminaire 0.5 kg. Grupo free from the security fotobiológica.

BODY MATERIAL

Stainless steel

APPLICATION

Indoor courtesy lighting, Indoor decorative lighting

PACKAGING CONTENTS

3 Units + 1 power supply

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS/W

250 lm/4,9W

IP RATING

IP20

ELECTRICAL CLASS

Type 2

OPTICS

Translucent

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

No

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

230 V~

L70 (°C)

25,000 h at 25 °C

POWER (W)

4.9 W

COLOR TEMPERATURE (K)

3100 K

COLOR TYPE

WW

POWER SUPPLY DIMENSIONS (MM)

42.2x40.2x22 mm

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

51 lm/W

SERVICE LIFE

25.000 h

CRI

80

LUMENS (LM)

250 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Semi-flush mount (wall, floor)

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

2 years 25,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.364

PRODUCT NET WEIGHT

0.364

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053093993

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

50

PACKAGING WIDTH

180

PACKAGING LENGTH

240

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2.16

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.364

PACKAGING WEIGHT UNIT

KGM