

## LedFlex 810.38 6500 K IP65

REF. 81038100-986



### BASIC INFORMATION

#### APPLICATION

General lighting, Indoor  
decorative lighting

#### PACKAGING CONTENTS

1 unit (5m)

## TECHNICAL INFORMATION

### IP RATING

IP65

### DRIVER INCLUDED

No

### LUMENS (LM)

10450 lm

### OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

### L70 (°C)

30,000 h

### LUMENS/W

10450 lm/96W

### COLOR TEMPERATURE (K)

6500 K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### OPTICS

General

### CONTROL

PWM

### COLOR TYPE

CW

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### CRI

80

### LIGHTING EFFICIENCY (LM/W)

108,9 lm/W

### POWER (W)

96 W

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Hardware

## REGULATIONS

### WARRANTY

3 years

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT  
0

UNITARY PACKAGING WEIGHT  
UNIT  
KGM

PACKAGING MEASUREMENT  
UNIT  
MMT

UNITARY PACKAGING WIDTH  
0

PACKAGING EAN  
8421053204979

PACKAGING VOLUME  
1200

UNITARY PACKAGING LENGTH  
0

UNITS CONTAINED PACKAGING  
1

PACKAGING VOLUME UNIT  
MMQ

UNITARY PACKAGING VOLUME  
0

PACKAGING HEIGHT  
2

PACKAGING GROSS WEIGHT  
409.2

UNITARY PACKAGING GROSS  
WEIGHT  
0.409

PACKAGING WIDTH  
24

PACKAGING NET WEIGHT  
0.409

PRODUCT NET WEIGHT  
0.409

PACKAGING LENGTH  
25

PACKAGING WEIGHT UNIT  
KGM