

MD-36 High Ceilings PIR+LUX SR surface DALI-2 Master white IP54

REF. 89207438-230



BASIC INFORMATION

DESCRIPTION

Surface-mounted PIR motion and brightness detector. The recommended installation height is 12 m, with a maximum height of 14 m. It has a detection angle of 360° and an opening angle of 90°. The tangential detection range is 36 m and the radial detection range is 14 m.

The brightness regulation range is 2 - 1000 lux and the timing range is 5 s - 15 min. The configuration of the detector is done through potentiometers and remote control.

It features a TEACH operating mode. Possibility of interconnection between sensors via DALI. The control protocol is DALI-2 Master. The number of adjustable luminaires via the DALI bus is 30 (1 group).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, IP 54 protection rating, and dimensions: 95 x 95 x 65 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2 Master

IP RATING

IP54

RAL

9003

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

4

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342107

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.254

PRODUCT NET WEIGHT

0.164

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342107

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1785600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.254

PACKAGING NET WEIGHT

0.164

PACKAGING WEIGHT UNIT

KGM