

## Luminaire P3 18,4W 4000K with detector 8m HF+LUX and emergency IP54

REF. 89164000-184



### BASIC INFORMATION

#### DESCRIPTION

Luminaire with integrated HF detector and emergency, power 18.4 W, luminous flux of 2188 and color temperature 4000 K. The emergency mode duration is 3 hours according to standard EN 60598-2-22. The maximum installation height is 4m and the installation is surface-mounted. The detection range is 8m and the detection angle is 360°.

The brightness regulation range is 2 - 2000 lux and the timing range is 5 s - 15 min.

Allows for the interconnection of master/master and master/slave luminaires.

The power supply voltage is 220 - 240 VAC. The operating temperature is: -10 - 40 °C.

Protection degree IP 54 and IK White and dimensions: Ø 400 x 142 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

#### FINISH

White

#### ETIM CLASS

EC002892

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### IP RATING

IP54

### POWER SUPPLY (V~)

220/240 V~

### IK CLASSIFICATION

03

### MAXIMUM POWER (W)

400

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053402610

### UNITARY PACKAGING GROSS WEIGHT

0.922

### PACKAGING LENGTH

410

### UNITARY PACKAGING HEIGHT

0

### PRODUCT NET WEIGHT

0.922

### PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING VOLUME

2325323

### UNITARY PACKAGING LENGTH

0

### PACKAGING EAN

8421053402610

### PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITS CONTAINED PACKAGING

1

### PACKAGING GROSS WEIGHT

1.628

### UNITARY PACKAGING VOLUME

0

### PACKAGING HEIGHT

410

### PACKAGING NET WEIGHT

0.922

### UNITARY PACKAGING VOLUME UNIT

MMQ

### PACKAGING WIDTH

150

### PACKAGING WEIGHT UNIT

KGM