

Complete set with 2 schuko socket outlets, 2 UPS sockets and plate for 4 RJ45 connectors white S400 Top

REF. 42602240-130



BASIC INFORMATION

DESCRIPTION

In a minimalist design and finishes in white tones tone, with the kit of desk top of Simon 400 Top will obtain the maximum functionality for its mechanism, in a compact design that adapts to all types of spaces. It consists of 2 socket-outlets, 2 Schuko sockets with system UPS/UPS (uninterruptable power supplies) and a plate for 4 RJ45 connectors. Designed for flush installation, is made of anodised aluminium and thermoplastic self-extinguishing halogen-free, which prevents the flame spread and toxicity by smoke in case of fire. Compatible with a voltage of 250 V of power and 16 A, is connected to figure Wieland gst 18 i with 3-pole male and its dielectric strength is 2000 V at 50H per minute, with has a insulation resistance > 5 M Ω at 500 V. Optimice the space of your work area getting in funionalidad and connectivity solutions thanks to this kit Simon 400 Top

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9016

NUMBER OF RJ45 WINDOWS

4

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

SNAP-FIT TYPE

Keystone I, II and Systimax

NUMBER OF SOCKETS

2 sockets for standard current circuit and 2 sockets for stable current circuit (UPS)

NUMBER OF UPS SOCKET OUTLETS

2

VERSION

6 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE

Suitable for fixing to furniture.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053196045

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053196045

PACKAGING VOLUME

3562500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

330

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

125

PACKAGING NET WEIGHT

1.2

UNITARY PACKAGING GROSS WEIGHT

1.2

PACKAGING LENGTH

95

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.2