POINT 56 Spotlight Mini Rail 4000 K Flood DALI Black

REF. **92061312-488**



BASIC INFORMATION

FINISH	MATERIAL	PACKAGING CONTENTS
Black	Aluminium	1 Unit
BODY MATERIAL	**APPLICATION**	**ETIM CLASS**
Aluminium injection moulding	Domestic,Office,Retail,Hotel,Contract	EC001744

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20

OPERATING TEMPERATURE RANGE (ºC)
0 - 35 ºC

POWER SUPPLY (V~)
220/240 V~

RAL
9005

COLOR TEMPERATURE (K)
4000 K

CONTROL
DALI2

CHROMATICS CRI ICONS



CRI
90

DIRECTIONAL
Yes

DRIVER INCLUDED
Yes

ELECTRICAL CLASS
II

ENERGY EFFICIENCY
A+

L70 (ºC)
150000h at 25ºC

L90 (ºC)
40000h at 25ºC

COLOR TYPE
CW

LIGHTING EFFICIENCY (LM/W)
hasta 79 lm/W

LUMENS (LM)
1050 lm

NUMBER OF LUMINAIRES
1

MACADAM STEPS
<3 Step MacAdam

OPTICS
Flood 30º

POWER (W)
14 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Rail

REGULATIONS

EAC MARKED
No

ECORRAE MARKED
Yes

WARRANTY
5 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8436547052462

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.58

PRODUCT NET WEIGHT
0.4

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8436547052462

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
83

PACKAGING WIDTH
180

PACKAGING LENGTH
298

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
4452120

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.44

PACKAGING NET WEIGHT
0.4

PACKAGING WEIGHT UNIT
KGM