

SUB-D25 connector (parallel port) female with trim plate white Simon K45

REF. K104A/9



BASIC INFORMATION

DESCRIPTION

The connections are increasingly important in our day-to-day life and, above all, in our work stations. We need to be quick and to achieve the best results in each occasion. At times, we need to that this information is swap so bidirectional and for this Simon brings us this SUB-D25 connector parallel port. It is a female connector with white trim plate in colour. It is composed of 2 elements and has 4 modules. It is a mechanism very versatile, since it can be placed both in surface-mounted and flush-mounted, while it is necessary to weld for the terminal connection. This connector for multimedia connections is part of the series K45. A series with countless combinations for your installations and with an objective firm: The supply to the spaces professionals from the best applications for workplace solutions on the market, always convenient, faster and safer.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Female SUB-D25 connector (parallel port)

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 30 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

CONNECTOR TYPE

Sub-D25

NUMBER OF WIRES

25

NUMBER OF CONTACTS

25

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

2 elements

RAL

9003

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.038

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436045446

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0.19

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.19

UNITARY PACKAGING GROSS
WEIGHT

0.038

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140