

Teleblock telescopic profile with manual elevation 2 elements aluminium Simon K45

REF. KTL202



BASIC INFORMATION

DESCRIPTION

Do you know the series Simon K45? If you have a business and you want to improve the workplace solutions in your workplace, this collection is the indicated for you. We present you this Teleblock telescopic profile with manual elevation of 2 elements of aluminium and black finish, its dimensions are 103 x 60 x 242 millimetres and has two elements and two modules, this product is suitable for flush mounting in furniture. It has a profile in anodised aluminium, which has a fastening bracket and top and bottom closure. It is manufactured in thermoplastic and self-extinguishing halogen-free, preventing flame spread in case of fire and low toxicity patient. This profile is supplied with 1 blind plate and 2 plates including 22.5x45 millimetres for a more effective internal distribution of cabling. We recommend, so that the installation is complete, combining it with the cover and trim frame (refs. KTLA1 / 14 or KTLA1 / 31). In addition to this version, we also have versions of this profile in 2, 3, 4, 5 and 6 elements. Just consult our catalogue.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Simon K45 range functions and possible to combine with the Simon Electrical Wiring range.

PACKAGING CONTENTS

Telescopic profile with manual elevation, non-slip joints, metal separator, 2 ground connections, 3 blind plates, (1 wide and 2 narrow), fastening thread and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the installation of the product it must be combined with the cover and trim frame (refs. KTLA1/14 or KTLA1/31).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the silicone gasket on the cover that prevents the entry of external elements when there are no connections. Yes, thanks to the silicone gasket on the cover that prevents the entry of external elements when there are no connections.

AVAILABLE IN

Available in 2, 3, 4, 5 and 6 elements

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Ensured by the fixing of the metal separator in the rail enabled in the bracket for this purpose.

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP4X

KIT AVAILABILITY

Yes

LINKABLE

No

NUMBER OF LOWER ENTRANCES

1 inlet, with the possibility for 6-cable access through the lower part of the profile via the K20/14 plate. The profile is supplied with the modular lower part to allow access of a variable quantity and type of cabling.

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF MODULES

2 modules

MONOBLOCK

No

RAL

7021

RECESS DIMENSION (MM)

Ø 114 mm

SPACE FOR CABLING DISTRIBUTION

The profile is supplied with 1 blind plate and two 22.5 x 45 mm plates, for a more effective internal distribution of cabling.

VERSION

2 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS

Through the space enabled in the lower part of the profile.. Entry for corrugated tube or cable gland, fast-connection connectors, electrical wiring leads, voice, data and multimedia cabling through specific plates.

REMOVAL OF COMPONENTS

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening the fastening thread supplied with the Simon K45 Teleblock telescopic profile.

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for embedding in furniture.

OPENING ORIENTATION

Top and bottom.

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Its design allows integration in any type of furniture, combining the telescopic profile with the cover and decorative frame (ref. KTLA1/14 black finish, ref. KTLA1/31 matte chrome finish)

MOUNTING WITHOUT ACCESSORIES

The telescopic profile is supplied with all necessary installation materials, including the fastening bracket, without needing additional references for attachment.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436052239

PRODUCT NET WEIGHT

0.975

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

13332200

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436052239

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.954

UNITARY PACKAGING VOLUME

13332200

PACKAGING HEIGHT

140

PACKAGING NET WEIGHT

0.975

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

214

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.975

PACKAGING LENGTH

445