

Service cover for 8 elements for installation in concrete floor or raised floor graphite Simon 500 Cima

REF. 52054104-038



BASIC INFORMATION

DESCRIPTION

Elegance and sophistication with the Service cover of 8 elements for installation in concrete floor or raised floor within the collection Simon 500 Cima. With delicate finishes in Graphite, this service cover integrates seamlessly into the space and fitting into any type of room, thanks to its simple and minimalist finishes. Made of halogen-free thermoplastic, it guarantees the security necessary in case of fire to encourage the no flame propagation or toxicity by smoke. It is also perfectly compatible with voice and data connectors and separates constantly the electrical cabling and Multimedia, preventing electromagnetic interference and transmission errors. One of the features of the service cover Simon 500 Cima, is the new being configurable according to the needs of each space. Once again, the Simon 500 Cima collection combines innovation, design and functionality in a single product.

FINISH

Graphite

PACKAGING CONTENTS

Service cover and installation
manual

ETIM CLASS

EC001903

MATERIAL

Plastic

REMARKS

Once the product has been installed, you have the option to combine it with the flush-mount trim cover (ref.52053104-038) in cases where you do not install the same floor covering.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

AVAILABLE IN

2, 4, 6, 8 and 12 elements

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

8 modules

RAL

7021

RECESS DIMENSION (MM)

170 x 265 mm

VERSION

8 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 14 and 54 mm

NUMBER OF COVER OPENING POSITIONS

2

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using fastening claws on the concrete floor tray or the raised floor tile (provided in the service cover)

CAN BE INSTALLED IN TRAY

Plástica y metálica

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

In raised floor and concrete floor

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053101650

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.19

PRODUCT NET WEIGHT

1.19

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053101650

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

75

PACKAGING WIDTH

186

PACKAGING LENGTH

282

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.934

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.19

PACKAGING WEIGHT UNIT

KGM

