

## 729.60 60x60 Low Glare Dip Switch DALI2

REF. 72960333-687



### BASIC INFORMATION

#### DESCRIPTION

Modular LED luminaire 729, 595x595mm aluminium body with microprismatic diffuser for uniform glare-free lighting (UGR<19). 3000K / 5000K CCT, CRI80, 3900lm, 114 lm/W. DALI-2 driver. Installation: suspended, recessed or surface mounted.

#### FINISH

White

#### APPLICATION

General lighting

#### MATERIAL

Aluminium

#### ETIM CLASS

EC002892

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### IP RATING

IP20

### OPERATING TEMPERATURE RANGE (°C)

-20...+35

### POWER SUPPLY (V~)

220/240 V~

### CONTROL

DALI2

### OPTICS

Diffused

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2011/65/UE RoHS + post. mod. | EN 60598-2-2:2012 | EN IEC 55015:2019 + A11:2020 | EN 62493:2015 | EN 61547:2009 | EN 62717:2017 + A2:2019 | EN IEC 61000-3-2:2019 + A1:2021\*1 | EN IEC 63000:2018 | EN 61000-3-3:2013 + A1:2019 + A2:2021

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053370193

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

2

### PRODUCT NET WEIGHT

1.75

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053370193

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

35

### PACKAGING WIDTH

690

### PACKAGING LENGTH

690

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

16663500

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

1.75

### PACKAGING WEIGHT UNIT

KGM