Extension 1.5 metres for square aluminium column with 2 sides Simon K45

REF. **ALK22P15/8**



BASIC INFORMATION

DESCRIPTION

Extension of 1.5 metres for pole of 2 sides oval aluminium of the series Simon K45. This pole has dimensions of 1500 x 80 x 80 mm and to ensure its robustness, just you can combine one extension per pole. Made in anodised aluminium, follow the regulation UNE-EN 50.085-2-4-: 2006 and extension is a perfect for use in rooms with a temperature between -25º and the most of 120 ° C, so it is ideal for use in any type of climatology. If you want to clean this extension and make it in perfect condition, just use a soft and dry cloth, forgetting to use any cloth and / or abrasive cleaner containing any quantity (QTY.) chlorine. The columns of the series Simon K45 fixing to the slab by applying pressure, and it is not necessary to screw them together to the floor, that is, without the need for screwing to concrete floor or the slab.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000795

MATERIAL

Aluminium

PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

AVAILABLE IN
2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (ºC)
+120º C

EARTHING RESISTANCE
< 0.05 ?

ELECTRICAL PROPERTIES
With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING
Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

HEAT RESISTANCE (ºC)
+650ºC (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
5 MOhms at 500 V.

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (ºC)
-25 a 120º C

VERSION
2-sided, (Square)

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Using connecting pins

INSTALLATION DIRECTION
Vertical

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436050594

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
3.4

PRODUCT NET WEIGHT
3.4

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436050594

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
88

PACKAGING WIDTH
119

PACKAGING LENGTH
1520

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
15.917

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
3.4

PACKAGING NET WEIGHT
3.4

PACKAGING WEIGHT UNIT
KGM