

Customisable in-desk set with cover and brush, 3 German socket outlets and 3 empty elements aluminium Simon 400

REF. 44603000-133



BASIC INFORMATION

DESCRIPTION

Kit within the table customizable and belonging to the series Simon 400, finished in aluminium colour. With cover, brush strip, 3 bases for Schuko socket outlets and 3 empty elements and is capable of withstanding a heat of over 70, approximately. It is a kit enclosure, manufactured in painted steel profile of anodised aluminium and the covers and fastenings are manufactured in self-extinguishing thermoplastic and halogen-free, a material that provides security since which guarantees is a low level of toxicity and the no-propagation of the spread in case of fire. It is possible to recess in furniture and is fixed by the claws that are supplied or using screws, through the holes available. Its cleaning is very easy to perform since it will only need to use a dry and soft cloth, without resorting never with abrasive cleaners or cloths containing chlorine.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

Schuko

NOMINAL VOLTAGE (V~)

250 V~

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

RAL

9006

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

IP RATING

IP30

NUMBER OF REAR ENTRANCES

3

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RECESS DIMENSION (MM)

318 x 175 mm (± 2mm)

NUMBER OF POSSIBLE ELEMENTS

3

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

NUMBER OF SOCKETS

3 sockets for standard current circuit

VERSION

6 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

REMOVAL OF COMPONENTS

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45°

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053196618

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.95

PRODUCT NET WEIGHT

1.95

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053196618

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

365

PACKAGING WIDTH

192

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

6657600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.95

PACKAGING WEIGHT UNIT

KGM