

818.36 1415mm three-phase track 4000K Opal On-Off CRI90 White

REF. 81836030-794



BASIC INFORMATION

DESCRIPTION

818 individual linear LED luminaire suspendida mediante cables de acero, with extruded aluminium body y finished in negro. Length 1415 mm, equipada con diffuser opal y LED module with 4000K con CRI CRI80. Ofrece un luminous flux of 4450 lm con una power of 43W y an efficacy of 103 lm/W. Control On-Off, supply 220-240V, ideal for oficinas, comercios y indoor spaces where functional and efficient lighting is required.

MATERIAL

Aluminium

APPLICATION

General lighting

ETIM CLASS

EC001744

REMARKS

Includes installation accessories.

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

0...+35

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

COLOR TYPE

NW

OPTICS

Opal

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053378199

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

4.065

PRODUCT NET WEIGHT

3.49

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053378199

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

145

PACKAGING LENGTH

1430

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

33176000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

4.065

PACKAGING NET WEIGHT

3.49

PACKAGING WEIGHT UNIT

KGM