

Linear luminaire 5150 BT Mesh 42W 4000K with detector 24GHz 8m HF+LUX IP65

REF. 89392620-424



BASIC INFORMATION

DESCRIPTION

Watertight luminaire with integrated HF detector and Bluetooth connectivity. Power is 42.4 W, luminous flux is 5940 lm and colour temperature is 4000 K. Maximum installation height is 4 m, surface-mounted. Detection range is 8 m and detection angle is 360°.

The light-level adjustment range is 2 - 2000 lux and the timing range is 5 s - 60 min. The luminaire is configured via a Bluetooth app. Luminaires can be interconnected via Bluetooth mesh.

Supply voltage is 220 - 240 VAC. Operating temperature: -20 - 40 °C.

Protection rating IP 65 and IK 07, dimensions: 1500 x 87 x 58 mm.

5-year warranty.

For more product information, visit the STEINEL website by clicking [here](#)

FINISH

Grey

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

IP RATING

IP65

CONTROL

BT

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053465714

UNITARY PACKAGING GROSS WEIGHT

0

PACKAGING LENGTH

1695

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

1.77

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053465714

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

2.2

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING NET WEIGHT

1.77

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

114

PACKAGING WEIGHT UNIT

KGM