


Voice and data flat plate for 1 element without dust cover
for 2 RJ45 compatible other manufacturers white Simon
K45

REF. KB076/9



BASIC INFORMATION

DESCRIPTION

Model of plate for 1 and 2 Connectors KB076 / 9 of the range of professional Components and elements Simon K45, compatible with different types of parts of the same Series of components. Plate Voice and data plate without dust cover for 1 Element for 2RJ45 with compatibility with other manufacturers and Keystone snap-fit I, II, ATT ® / Avaya ®. Model individual version of module means, in colour and finishes White in colour and incorporates halogen-free thermoplastic components that Guarantees no flame propagation in case of fire and low toxicity in the In the case of smoke, ensuring maximum security professionally. It allows the combination with Element 90° positioner (ref. K66) to guide the plate In vertical position, in voice and data plate in vertical enclosures. It measures Values 45x45mm and a depth of 8 mm, easy to adapt to different environments. Work professionals and home.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate without dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

Plate for 1 and 2 RJ45 connectors

COMPATIBLE WITH CONNECTORS

Simon®, ADC Krone® Series KM8 Keystone, AMP netconnect® Series SL110 and SL Tool less, BeldenCDT® Series Giga Flex Keystone, Ersys®, General Cable®, Molex®, Nexans® Series essential Keystone,Ortronics® Series Clarity TechChoice Keystone, Panduit® Series Netkey, R&M® Series Advance Cat6A (R509508, R509509), Rit®, Siemon® Series MAX Keystone, Systimax® and manufacturers of RJ45 with snap-fit based on the Keystone I and II format.

RJ45 CONNECTORS

Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

DUST PROTECTION

No

DUST SHUTTER

No

FORMAT

RJ45

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF MODULES

Half

PLATE TYPE

Flat

RAL

9003

RJ45 ADAPTOR MODULE

Included in voice and data plate

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436065758

PACKAGING VOLUME

0.911

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

70

PACKAGING GROSS WEIGHT

4.62

UNITARY PACKAGING GROSS
WEIGHT

0.011

PACKAGING WIDTH

93

PACKAGING NET WEIGHT

0.22

PRODUCT NET WEIGHT

0.011

PACKAGING LENGTH

140

PACKAGING WEIGHT UNIT

KGM