

VGA HD15 connector female with screw terminal connection system and built-in plate graphite Simon 27 Play

REF. 2700091-038



BASIC INFORMATION

DESCRIPTION

Connector in graphite colour VGA HD15 female, from the Simon 27 Play series, with screw terminal connection system and built-in plate. It works by insertion and can be installed both recessed and surface-mounted, located in rooms with a temperature between 5 and 40°C, approximately, although it is able to withstand extreme temperatures of -25 to 50°C. It measures 45 x 45 mm and it is manufactured with metallic components halogen-free and thermoplastic trim, a material very easy to clean: Just wipe it with a soft cloth and slightly moistened in soapy water, without having to use never abrasive cloths or cleaners containing chlorine, as they could damage it. It has 2 modules and the maximum recommended length of cabling is 20 meters, with a cross-section of 0.2 to 0.5 mm and the stripping of 5 mm, approximately.

FINISH

Graphite

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

VGA HD15 female connector and instruction sheet

ETIM CLASS

EC000018

REMARKS

Recommended maximum cable length: 20 metres. For more information see the product instruction sheet.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

NUMBER OF CONNECTORS

1

CONNECTOR TYPE

VGA

NUMBER OF CONTACTS

15

NUMBER OF POSSIBLE ELEMENTS

1 element

FORMAT

VGA

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Insertion

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

TYPE

HD15

VERSION

Single

NUMBER OF WIRES

10

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

5

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and Centralisations

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + EN 50581:2012

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053117699

PRODUCT NET WEIGHT

0.05

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

337500

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053117699

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

60

PACKAGING NET WEIGHT

0.05

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

75

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.05

PACKAGING LENGTH

75