Voice and data flat plate for 1 element without dust cover for 1 Panduit® RJ45 connector white Simon K45

REF. **K069/9**



BASIC INFORMATION

DESCRIPTION

In its permanent search for solutions according to the notable and rapid technological advances, Simon designs its ranges and collections of connections to be perfectly compatible with the majority of the best brands sold on the market. The voice and data plates of the K45 range are specially designed for assembly in housings of the SIMON CONNECT K45 range, using direct snap-fit. They can also be installed in the CIMA Range using the plates adaptable to the system being installed. The Simon Connect system offers a complete solution with a wide range of angled and flat plates with connectors of proven quality. This plate is, among others, perfectly compatible with Panduit ® connectors, for which it is specially designed. This is a flat voice and data plate without dust cover with 1 element for 1 Panduit® RJ45 connector. White finish from the Simon K45 range. Compatible with Panduit ® RJ45 Connectors. Single position. When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, mechanism holder trunking) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position. Dimensions 45 x 45 mm and depth. 8.5 mm Halogen-free thermoplastic that ensures no flame propagation in case of fire and low toxicity in case of smoke. Fully complies with the regulations on extreme temperatures. UNE-EN 60670-1: 2006 (-5 to +60 ºC + 60 ° C). Clean with a soft, dry cloth, do not use abrasive products or cleaners.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate without dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

COMPATIBLE WITH CONNECTORS
Panduit® Mini-Com Series.

RJ45 CONNECTORS
Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
No

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
9003

RJ45 ADAPTOR MODULE
Included in voice and data plate

SNAP-FIT RJ45 PLATES
Panduit® RJ45 connectors

SNAP-FIT TYPE
Panduit® RJ45 connectors

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
45570

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.01

PRODUCT NET WEIGHT
0.01

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436025073

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.2

PACKAGING NET WEIGHT
0.2

PACKAGING WEIGHT UNIT
KGM