

On-desk set with 2 German socket outlets, 2 UPS sockets and plate for 4 RJ45 connectors aluminium Simon 400

REF. 42602240-133



BASIC INFORMATION

DESCRIPTION

Unified in the minimum space all the functions, with the kit of desk top of Simon 400. With a compact design of clean lines and finishes in aluminium, this kit consists of 2 Schuko socket outlets, 2 UPS (uninterruptable power supplies) and a plate with 4 RJ45 connectors, a greater number of functions in a reduced space to optimize its working area. Recessed and installation manual elevation, it is compatible with a voltage of 250 V of power and 16 A of intensity, connected to figure Wieland, and with connectors compatible with Keystone ports. Moreover, its dielectric strength is 2000 V at 50H per minute and has a insulation resistance $> 5 \text{ M}\Omega$ at 500 V. Made from aluminium profile and covers and fastenings in self-extinguishing thermoplastic and halogen-free, protects the flame spread and toxicity by smoke, in case of fire. Innovation and functionality that optimizes space with Simon 400.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP30

RAL

9006

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NUMBER OF RJ45 WINDOWS

4

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

FORMAT

Schuko

SNAP-FIT TYPE

Keystone I, II and Systimax

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

NOMINAL VOLTAGE (V~)

250 V~

NUMBER OF SOCKETS

2 sockets for standard current circuit and 2 sockets for stable current circuit (UPS)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

NUMBER OF UPS SOCKET OUTLETS

2

CURRENT (A)

16 A

VERSION

6 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053196052

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.2

PRODUCT NET WEIGHT

1.2

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053196052

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

330

PACKAGING WIDTH

125

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3918750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.2

PACKAGING WEIGHT UNIT

KGM