2-way switch 10AX 250V~ with built-in pilot light and fast terminal connection system ivory Simon 27 Play

REF. **27212-62**



BASIC INFORMATION

DESCRIPTION

This 2-way switch 10A and 250 volts is part of the Simon 27 Play series products. It is designed to reroute or directly cut the power of a circuit, allows you to control a lighting point from two different controls and has a luminous light. Stands out for its quick terminal connection system. It is very easy to install, by means of recessed or directly in surface-mounted, it consists of two modules and has dimensions of 45 x 45 millimetres. It has a rocker operation so that it is very simple, interactive and user-friendly for the user, it is also available in ivory finish, a colour that will give elegance to the room where it is. In this way, Simon products will not only comply perfectly the function for the that have been created, but are converted to decorative elements fully integrated in the places where it is installed. The components of this device are the components, but also with halogen-free thermoplastic insulation and thermoset trim. This increases the security of the final product and ensures a long service life.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC001590

REMARKS

Can be combined with article 31802-31 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

CONSUMPTION INDICATOR (MA)

0.55 mA

NUMBER OF POSSIBLE ELEMENTS

1 element

INDICATOR FUNCTION

Yes

CURRENT (A)

16 AX

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Pivoting

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
11

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN 60669-1:2018|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
1235960

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.049

PRODUCT NET WEIGHT
0.049

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053035689

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
53

PACKAGING WIDTH
106

PACKAGING LENGTH
220

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1235960

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.485

PACKAGING NET WEIGHT
0.49

PACKAGING WEIGHT UNIT
KGM