

Real time clock and twilight sensor BT Mesh white IP54

REF. 89262140-330



BASIC INFORMATION

DESCRIPTION

Twilight sensor and real-time clock for Bluetooth sensors and luminaires. The brightness regulation range is 1 - 1000 lux. The detector configuration is done via Bluetooth application. It has a TEACH operating mode. Possibility of interconnection between sensors and luminaires via Bluetooth Mesh. The control output is On/Off, and the maximum switchable power is 1000 W (250 W LED). The power supply voltage is 220 - 240 VAC. White finish, protection degree IP 54, and dimensions: 95 x 95 x 38 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000189

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

1000

CONTROL

Bluetooth Slave

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053399750

UNITARY PACKAGING GROSS WEIGHT

0.185

PACKAGING LENGTH

75

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.125

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053399750

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.185

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

155

PACKAGING NET WEIGHT

0.125

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

90

PACKAGING WEIGHT UNIT

KGM