

Modular Luminaire Simon 720 Advance M4 120x30 BIO 1-10 V

REF. 72061140-880



BASIC INFORMATION

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

4000 lm

IP RATING

IP44

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

4000 lm/ 34 W

OPERATING TEMPERATURE RANGE (°C)

0 to 40° C

L70 (°C)

100.000 h at 25 °C

OPTICS

Translucent

POWER SUPPLY (V~)

100/240 V~

L90 (°C)

40.000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

COLOR TEMPERATURE (K)

2700K – 5700K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

34 W

CONTROL

1-10 V

LIGHTING EFFICIENCY (LM/W)

118 lm/w

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted | Plaster ceiling | Concealed profile | Semi-concealed profile

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.62

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053091265

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

300

PACKAGING LENGTH

1200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

23400000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

5

PACKAGING WEIGHT UNIT

KGM