

Floodlight Home 2 BT Mesh 13,8W 3000K with detector 10m 180° PIR+LUX black IP54

REF. 89393601-133



BASIC INFORMATION

DESCRIPTION

Projector with PIR detector and Bluetooth connectivity. The power is 13.8 W, the luminous flux is 1550 lm and the color temperature is 3000 K. The maximum installation height is 4m and the installation is on wall (surface). The detection range is 10m and the detection angle is 180 °. The brightness regulation range is 2 - 2000 lux and the timing range is 10 s - 15 min. The configuration of the luminaire is done through a Bluetooth application. Possibility of interconnection between luminaires via Bluetooth mesh. The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C. Protection degree IP 44 and IK 03 and dimensions: 161 x 180 x 218 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Black

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

IK CLASSIFICATION

03

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053400678

UNITARY PACKAGING GROSS WEIGHT

0.91

PACKAGING LENGTH

245

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.576

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053400678

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.91

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

225

PACKAGING NET WEIGHT

0.576

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

146

PACKAGING WEIGHT UNIT

KGM