

Modular luminaire 720 Advance M4 60x60 Low Glare NW 1-10V

REF. 72060140-684



BASIC INFORMATION

DESCRIPTION

With optimum micro prismatic and a lighting of a white for NW neutral (4000 K), the luminaire 720 modular Advance M4 60 x 60 of the collection Simon for indoor lighting, it to any space the guarantee of the highest quality lighting linked to the most efficient energy savings. With the latest LED technology, this luminaire get a energy savings of up to 20%, with a service life of 100,000 hours for the L70 at 25 ° C and L90 40.000 for. Its light flux light is 3400 lm / 28 W and is compatible with a voltage of 100.-240 Volt and 50-60 Hertz rate. Includes system of adjustment 1-10 V, and is designed for installation in false ceiling, visible hardware by flush mounted or surface-mounted. These features combined to its finishes in white and the latest technology in lighting, make this modular luminaire in the ideal option to achieve that each space with light us shine.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

121 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Tipo 2

LUMENS (LM)

3400 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

3400 lm/28W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Microprismatic

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

CONTROL

1-10 V

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

28 W

CRI

82

COLOR TYPE

NW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
82

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

INSTALLATION TYPE

False ceiling, visible hardware

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053191781

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053191781

PACKAGING VOLUME

0.234

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

65

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

600

PACKAGING NET WEIGHT

5

UNITARY PACKAGING GROSS
WEIGHT

5.62

PACKAGING LENGTH

600

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

5