

**Customisable kit with dual opening cover, brush, 4x USB
charger, 8 schuko socket outlets and 2 empty elements
white S400 Indesk Duo**

REF. 46624000-130



BASIC INFORMATION

DESCRIPTION

Among the devices for flush mounting in furniture from the Simon 400 Indesk Duo series, the customizable kit integrated into the table stands out, featuring a cover with two openings and a brush, a charger with 4 x USB ports, eight schuko socket bases for standard power circuit, and two empty elements for customization in white. Insulation resistance of >5 MO at 500 V, current intensity of 16 A, Wieland® gst18i connector with three aerial male poles with a 22 cm patch cord, voltage of 250 V~ and dielectric strength without drilling or contouring at 2000 V at 50 Hz for 1 minute are other of its characteristics. Why is this kit so durable and safe? Because of the outer painted steel, anodized aluminum profile, covers and fasteners made of self-extinguishing thermoplastic and halogen-free materials used in its structure, ensuring no flame propagation in case of fire and low toxicity in case of smoke emission.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

IK CLASSIFICATION

07

INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

-5...+60

TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9016

NUMBER OF REAR ENTRANCES

2

RECESS DIMENSION (MM)

318 x 175 mm (± 2mm)

NUMBER OF SOCKETS

8 sockets for standard current circuit

NUMBER OF USB CHARGERS

2

VERSION

12 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45° and 135°

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053273722

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

3.4

PRODUCT NET WEIGHT

3.4

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053273722

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

130

PACKAGING WIDTH

215

PACKAGING LENGTH

345

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

5722200

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

3.4

PACKAGING WEIGHT UNIT

KGM