

ARCH S Downlight Round 3000 K Spot DALI White

REF. 91532001-300



BASIC INFORMATION

BODY MATERIAL

Die-cast aluminium

PACKAGING CONTENTS

1 Unit

APPLICATION

Domestic, Office, Retail, Hotel, Contract

PACKAGING DIMENSIONS (MM)

16x224x171 mm

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

Yes

LUMENS (LM)

800 lm

IP RATING

IP43

DRIVER INCLUDED

Yes

NUMBER OF LUMINAIRES

1

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

II

MACADAM STEPS

<3 Step MacAdam

POWER SUPPLY (V~)

110/240 V~

ENERGY EFFICIENCY

A+

OPTICS

Spot 20°

RAL

9016

L70 (°C)

100000h at 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Class II

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

30000h at 25°C

POWER FACTOR (Φ)

> 0,9

CONTROL

DALI

COLOR TYPE

NW

POWER (W)

9 W

CRI

90

LIGHTING EFFICIENCY (LM/W)

111 lm/W

PHOTOMETRY ASSETS - POLAR



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Flush-mounted, Trimless

INSTALLATION TYPE

Surface-mounted

REGULATIONS

EAC MARKED

Yes

ECORRAE MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8436547037827

PACKAGING VOLUME

4567500

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

116

PACKAGING GROSS WEIGHT

1.2

UNITARY PACKAGING GROSS WEIGHT

1.2

PACKAGING WIDTH

171

PACKAGING NET WEIGHT

1.09

PRODUCT NET WEIGHT

1.09

PACKAGING LENGTH

224

PACKAGING WEIGHT UNIT

KGM