

Downlight 725.22 Flush mount NW General Aluminium

REF. 72522033-984



BASIC INFORMATION

DESCRIPTION

With this luminaire Downlight 755.22 flush mounted NW Advance GENERAL obtendremos a neutral and uniform lighting, perfect as general lighting for corridors, transit areas, or as a general lighting for commercial establishments. This piece has a stylish finished in aluminium and it is suitable to be flush mounted. Thanks to LED technology, with a power of 24 Watts we will have a light intensity of 2,300 lumens. A high power with a low cost of the electricity consumption, as we ensures 30,000 hours of light without any maintenance and without the quality of lighting we see deteriorada. When you have a general optics, the light is repartirá of a uniform by the whole room. Its control system is on - OFF, and for its power requires a power of 100 - 240 volts. This is a product very durable with which notaremos a great savings in energy savings of the light.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

2300 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 1

LUMENS/W

2300 lm/24W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3900 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

24 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

96 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

107

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.22

PRODUCT NET WEIGHT

1.22

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053116692

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

70

PACKAGING WIDTH

250

PACKAGING LENGTH

250

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4375000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.22

PACKAGING NET WEIGHT

1.22

PACKAGING WEIGHT UNIT

KGM