

# LANE 2400 linear luminaire On/Off HO Surface-mounted 3000 K Batwing White

REF. 91302008-300



## BASIC INFORMATION

### BODY MATERIAL

Aluminium

### PACKAGING CONTENTS

1 Unit

### APPLICATION

Domestic,Office,Retail,Contract

### ETIM CLASS

EC001743

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### DIRECTIONAL

No

### LIGHTING EFFICIENCY (LM/W)

hasta 97 lm/W

### IP RATING

IP20

### DRIVER INCLUDED

Yes

### LUMENS (LM)

5580 lm

### OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

### ELECTRICAL CLASS

I

### NUMBER OF LUMINAIRES

1

### POWER SUPPLY (V~)

220/240 V~

### ENERGY EFFICIENCY

A+

### MACADAM STEPS

<3 Step MacAdam

### RAL

9016

### L70 (°C)

100000h at 25°C

### OPTICS

Batwing 105°

### COLOR TEMPERATURE (K)

3000 K

### L90 (°C)

30000h at 25°C

### POWER FACTOR (Φ)

>0,9

### CONTROL

On/Off

### LIGHT BEAM APERTURE ANGLE (°)

105°

### POWER (W)

73 W

### CRI

90

### COLOR TYPE

NW

### CHROMATICS CRI ICONS

CRI  
90

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Surface-mounted/Suspended

## REGULATIONS

### EAC MARKED

No

### ECORRAE MARKED

Yes

### WARRANTY

5 years

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING WIDTH

0

### PACKAGING EAN

8436547033423

### PACKAGING VOLUME

16128000

### UNITARY PACKAGING LENGTH

0

### UNITS CONTAINED PACKAGING

1

### PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING VOLUME

0

### PACKAGING HEIGHT

80

### PACKAGING GROSS WEIGHT

4.95

### UNITARY PACKAGING GROSS WEIGHT

6.55

### PACKAGING WIDTH

84

### PACKAGING NET WEIGHT

4.5

### PRODUCT NET WEIGHT

4.5

### PACKAGING LENGTH

2400

### PACKAGING WEIGHT UNIT

KGM