

Cover for German double socket outlet mechanism with viewer and LED indicator orange Simon 500 Cima

REF. 50011041-072



BASIC INFORMATION

DESCRIPTION

Cover for the mechanism of socket Simon 500 Cima. It is Schuko, is available in orange colour and with dual viewer and indicator led. With 2 elements and 2 modules, this cover for plugs of the Simon 500 Cima series, needs to be combined with a double socket outlet and that has Schuko format. Complies with the regulations UNE 20315 standard / EN 60.998-2-3 and is made of halogen-free thermoplastic, a material that ensures a low toxicity in case of smoke and the no-propagation spread in case of fire. It is a cover socket suitable for both recessed and on surfaces with temperatures between -5 and 60 ° C and its cleaning is simple: Just you would have to use a soft, dry cloth and avoid abrasive cloths or cleaners that contain a percentage of chlorine in its formula.

FINISH

Orange

MATERIAL

Various

COMPATIBILITY

German double socket outlets
Simon 500 Cima

PACKAGING CONTENTS

Cover for German double socket outlet mechanism with viewer and LED light indicator and installation manual

ETIM CLASS

EC000011

REMARKS

Must be combined with a German double socket outlet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

Plate with viewer and LED light indicator, plate without viewer and as a replacement for plate with viewer

IP RATING

IP20

NUMBER OF MODULES

2

KIT AVAILABILITY

No

RAL

2009

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C in surface-mount wall installation and +90 °C in flush-mount wall installation

LED CONSUMPTION INDICATOR (MA)

0.55

VERSION

2 elements

FORMAT

Schuko

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

TYPE OF FASTENING

By direct snap-fit on the double socket outlet (no tools needed for fastening))

INSTALLATION TYPE

Suitable for surface or flush-mount installation

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053093566

PACKAGING VOLUME
1.201

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
52

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.028

PACKAGING WIDTH
105

PACKAGING NET WEIGHT
0.28

PRODUCT NET WEIGHT
0.028

PACKAGING LENGTH
220

PACKAGING WEIGHT UNIT
KGM

