

LedFlex 810.35 2700 K IP65 CRI90

REF. 81035100-992



BASIC INFORMATION

APPLICATION

General lighting, Indoor
decorative lighting

PACKAGING CONTENTS

1 unit (5m)

ETIM CLASS

EC002706

TECHNICAL INFORMATION

IP RATING

IP65

DRIVER INCLUDED

No

LUMENS/W

3800 lm/48W

OPERATING TEMPERATURE RANGE (°C)

-20 - 40 °C

L70 (°C)

30,000 h

OPTICS

General

COLOR TEMPERATURE (K)

2700 K

LIGHT BEAM APERTURE ANGLE (°)

120°

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

PWM

LIGHTING EFFICIENCY (LM/W)

79,2 lm/W

POWER (W)

48 W

CRI

90

LUMENS (LM)

3800 lm

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Hardware

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053202777

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053202777

PACKAGING VOLUME

1200

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

2

PACKAGING GROSS WEIGHT

426.4

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

24

PACKAGING NET WEIGHT

0.426

UNITARY PACKAGING GROSS
WEIGHT

0.426

PACKAGING LENGTH

25

PACKAGING WEIGHT UNIT

GRM

PRODUCT NET WEIGHT

0.426