

Cover for mechanism of the German double socket outlet with viewer graphite Simon 500 Cima

REF. 50011841-038



BASIC INFORMATION

DESCRIPTION

Cover for Schuko double socket outlet red viewer, of the collection Simon 500 Cima. Socket and cover tandem form the perfect for the Schuko socket outlet with dual viewer, in an attractive red colour that combines with all types of rooms. Made of thermoplastic materials and self-extinguishing halogen-free, adding extra security as it avoids flame spread in case of fire and to minimize the toxicity by smoke. The innovation in the collection Simon 500 Cima, giving the cover for bipolar socket outlet, an exhaustive signaling function that, thanks to the technology of Simon, you can locate its socket, when lack of lighting. With a size of 100 x 50 x 9 mm and a depth of 9mm, it is suitable to install it on the surface-mounted or flush-mounted according to their needs specific. The collection Simon 500 Cima is elegance, innovation and security.

FINISH

Graphite

MATERIAL

Plastic

COMPATIBILITY

German double socket outlets
Simon 500 Cima

PACKAGING CONTENTS

Cover for the mechanism of the
German double socket outlet
with viewer without LED light
indicator

ETIM CLASS

EC000011

REMARKS

Must be combined with a German double socket outlet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

Plate with viewer and LED light indicator, plate without viewer and as a replacement for plate with viewer

IP RATING

IP20

NUMBER OF MODULES

2

KIT AVAILABILITY

No

RAL

7021

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C in surface-mount wall installation and +90 °C in flush-mount wall installation

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

2 elements

FORMAT

Schuko

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

TYPE OF FASTENING

By direct snap-fit on the double socket outlet (no tools needed for fastening))

INSTALLATION TYPE

Suitable for surface or flush-mount installation

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053093597

PACKAGING VOLUME
1.201

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
52

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.026

PACKAGING WIDTH
105

PACKAGING NET WEIGHT
0.26

PRODUCT NET WEIGHT
0.026

PACKAGING LENGTH
220

PACKAGING WEIGHT UNIT
KGM

