Voice and data angled plate with dust cover for 1 element and 2 RJ45 connectors category 5e UTP black Simon K45

REF. **KB8095U/14**



BASIC INFORMATION

DESCRIPTION

The series Simon K45 presents the plate of voice and data tilted plate with dust cover and insertion tool composed of 1 element and 2 RJ45 category 5e FTP connectors, the piece is suitable for surface or flush mounting and has dimensions of 45x45 mm and a thickness of 46.5 mm with and perfect finishes in black. Also, is made of halogen-free metal components with self-extinguishing thermoplastic insulation to ensure that the flame spread notional is not in the event of a fire and a very low toxicity in case of smoke. If, in addition, you want to combine the voice and data plate in vertical enclosures, you'd need to use the 90º positioner to be able to guide the piece in vertical position. The best solutions of workplace solutions are at your disposal through the collection K45 of Simon, a collection designed to detail to meet even to the most demanding customers. Trust/Confident in one of the most dedicated and you the games.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Voice and data tilted plate with dust cover, direct modules for snap-fit connector and category 5e RJ45 UTP connectors

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-26 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 5e UTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
Yes

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Angled

RAL
7021

RJ45 ADAPTOR MODULE
Supplied with voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

287138

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.035

PRODUCT NET WEIGHT

0.035

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436040328

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

95

PACKAGING WIDTH

155

PACKAGING LENGTH

195

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2871375

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.35

PACKAGING NET WEIGHT

0.35

PACKAGING WEIGHT UNIT

KGM