

Luminaire RS 16 L S for E27 with detector PIR+LUX IP 44

REF. 89194000-600



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector, maximum power 60 W.

The maximum installation height is 4m and the installation is surface-mounted. The detection range is 8m and the detection angle is 360°.

The light intensity regulation range is 2 - 2000 lux and the timing range is 5 s - 15 min.

Allows interconnection of master/master and master/slave luminaires.

The power supply voltage is 220 - 240 VAC. The operating temperature is: -10 - 40 °C.

Protection grade IP 44 and IK 3 with dimensions: Ø 275 x 95 mm.

3-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

IK CLASSIFICATION

03

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053357248

UNITARY PACKAGING GROSS WEIGHT

1.73

PACKAGING LENGTH

300

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

1.73

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

10800000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053357248

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.794

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

300

PACKAGING NET WEIGHT

1.73

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

120

PACKAGING WEIGHT UNIT

KGM