

MD-20 180° PIR+LUX wall surface On/Off white IP54

REF. 89202135-230



BASIC INFORMATION

DESCRIPTION

PIR motion and brightness detector for surface wall. The recommended installation height is 2.5 m, with a maximum height of 2.5 m. It has a detection angle of 180° and an opening angle of 90°. The tangential detection range is 20 mm and the radial detection range is 4 m.

The luminosity regulation range is 2 - 1000 lux and the timing range is 5 s - 15 min. The detector configuration is performed via potentiometers and remote control.

It has a TEACH operating mode. Possibility of interconnection between master/master sensors up to 10 detectors. The control output is On/Off and the maximum switchable power is 2000 W (600 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, protection rating IP 54 and dimensions: 95 x 95 x 65 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

1.8

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053381960

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.25

PRODUCT NET WEIGHT

0.176

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053381960

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

125

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.25

PACKAGING NET WEIGHT

0.176

PACKAGING WEIGHT UNIT

KGM