

PD-12 HF+LUX BT Mesh recessed box IP white IP20

REF. 89214523-230



BASIC INFORMATION

DESCRIPTION

Recessed HF presence and light-level detector. Recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 140°. The tangential detection range is 12 m and the radial detection range is 12 m.

The light-level adjustment range is 10 - 1000 lux. The detector is configured via a Bluetooth app and web interface. The control protocol is IP.

Supply is standard PoE. Detector operating temperature: -20 - 50 °C.

White finish, IP 20 protection rating and dimensions: 103 x 103 x 61 mm.

5-year warranty.

For more product information, visit the STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

IP RATING

IP20

POWER SUPPLY (V~)

Standard PoE (IEEE 802.3af)

CONTROL

IP

OPERATING TEMPERATURE RANGE (°C)

-20...+50

RAL

9003

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

INSTALLATION TYPE

Flush box mounting

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053441152

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.25

PRODUCT NET WEIGHT

0.15

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053441152

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.25

PACKAGING NET WEIGHT

0.15

PACKAGING WEIGHT UNIT

KGM