

PD-25x3 Hallway HF+LUX BT Mesh recessed box On/Off black IP20

REF. 89215126-238



BASIC INFORMATION

DESCRIPTION

Presence and brightness detector for flush mounting HF. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 140°. The tangential detection range is 25 x 3 m and the radial detection range is 25 x 3 m.

The brightness regulation range is 2 - 2000 lux and the timing range is 5 s - 60 min. The detector configuration is done via bluetooth application.

It features a TEACH operating mode. Possibility of interconnection between sensors via Bluetooth. The control output is On/Off and the maximum switchable power is 2000 W (600 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C. Black finish, protection degree IP 20 and dimensions: 103 x 103 x 67 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Black

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9005

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342626

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.29

PRODUCT NET WEIGHT

0.177

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342626

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.29

PACKAGING NET WEIGHT

0.177

PACKAGING WEIGHT UNIT

KGM