# Customisable in-desk kit with lid and brush, 2 Schuko sockets and 3 empty modules, black, Simon 400 Indesk

REF. **44502000-138**



## BASIC INFORMATION

### DESCRIPTION

Kit within the table customizable, of the series Simon 400 Indesk, black in colour and has brush strip, cover, 2 SCHUKOS and 3 empty elements. It has dimensions of 295 x 185 x 85 mm and it is manual elevation and access to the cabling with brush strip. It has a current of 16 A and works with a power supply of 250V. It is a kit suitable for installation in flush mounted in furniture. To fix it, you can use the claws that incorporates the kit or do it through the screws, Drop in the holes available. For the cleaning of this kit you will have to use a soft and dry cloth and forget you of the cloths and / or abrasive cleaners containing chlorine in their formulation, as they could damage it and make it does not worked. It is made of painted steel the enclosure, the profile in anodised aluminium and the covers and fastenings in self-extinguishing thermoplastic and halogen-free.

### FINISH

Black

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

# TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with brush

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

### NUMBER OF POSSIBLE ELEMENTS
3

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

### NOMINAL VOLTAGE (V~)
250 V~

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9005

### NUMBER OF REAR ENTRANCES
3

### RECESS DIMENSION (MM)
273 x 175 mm (± 2mm)

### NUMBER OF SOCKETS
2 sockets for standard current circuit

### VERSION
5 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS
With brush

### CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

### REMOVAL OF COMPONENTS

### NUMBER OF COVER OPENING POSITIONS
1

### EXTINGUISHING (ºC)
+70 ºC (according to standard IEC 60670)

### TYPE OF FASTENING
By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME
Only with tool

### INSTALLATION TYPE
Suitable for recessed mount in furniture.

### OPENING ORIENTATION
At 45

### REMOVAL OF THE PLATE
Only with tool

### SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

# LOGISTICS INFORMATION

UNITARY EAN CODE
8421053196410

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.85

PRODUCT NET WEIGHT
1.85

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053196410

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
320

PACKAGING WIDTH
192

PACKAGING LENGTH
95

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
5836800

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.85

PACKAGING WEIGHT UNIT
KGM