Push-button switch with bell symbol 10A 250V~, built-in light and fast terminal connection system white Simon 31

REF. **31660-30**



BASIC INFORMATION

DESCRIPTION

White push-button switch from the Simon 31 series, with bell symbol, built in LED system and quick terminal connection. It works with a voltage of 250V and current of 10A and has has a rocker operation. This push-button switch can be combined with article 31802-31 if you need to replace the indicator light. Has 1 element and 2 modules and supports a cable section of 1.5 to 2.5 mm, with a wire stripping of 11 mm and can be installed perfectly in places with a temperature of between 5 and 40ºC, although it is capable of withstanding extreme temperatures of -25 to 50ºC, approximately. It complies with regulations UNE-EN 60669-1:2002 + A1:2003 + A2:2009 and is manufactured with metal components with halogen-free thermoplastic insulation and thermoset trim. It measures 64x65 mm and is cleaned with a soft cloth slightly moistened in soapy water, without the use of abrasive cloths or cleaners with chlorine.

FINISH

White

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000029

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Mechanism with rocker

REMARKS

Can be combined with article 31802-31 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 1,5 to 2,5 mm

CONSUMPTION INDICATOR (MA)
1 mA

NUMBER OF POSSIBLE ELEMENTS
1 element

INDICATOR FUNCTION
Yes

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Pivoting

NOMINAL VOLTAGE (V~)
250 V~

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
11

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.092

PRODUCT NET WEIGHT
0.092

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053006467

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
83

PACKAGING WIDTH
165

PACKAGING LENGTH
221

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3026595

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.915

PACKAGING NET WEIGHT
0.92

PACKAGING WEIGHT UNIT
KGM