

PD-12 HF+LUX BT Mesh recessed On/Off white IP20

REF. 89214113-230



BASIC INFORMATION

DESCRIPTION

Presence and luminosity detector for flush mounting HF. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 140°. The tangential detection range is 12 m and the radial detection range is 12 m.

The luminosity regulation range is 2 - 2000 lux and the timing range is 5 s - 60 min. The configuration of the detector is done via a Bluetooth application.

It has a TEACH operating mode. Possibility of interconnection between sensors via Bluetooth. The control output is On/Off and the maximum switchable power is 2000 W (600 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, protection degree IP 20 and dimensions: 103 x 103 x 100 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342510

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.326

PRODUCT NET WEIGHT

0.191

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342510

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

141

PACKAGING WIDTH

141

PACKAGING LENGTH

141

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2803221

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.326

PACKAGING NET WEIGHT

0.191

PACKAGING WEIGHT UNIT

KGM