

## Downlight 705.23 Directional WW Wide Flood 1-10V Aluminium

REF. 70523133-483



### BASIC INFORMATION

#### DESCRIPTION

Provide the highest quality to its lighting ambience or accent lighting, with the downlight 705.23 of Simon. With Wide Flood optics for a greater surface of light angle, and a colour temperature 3100 K for warm tone, this downlight is perfect for areas requiring a lighting wide, such as fitting rooms or reception areas, among others. With luminous light flux 1000 lumens for WW, and total luminaire consumption of 15.5 W, it is compatible with power Volt voltage 100-240 and 50-60 Hz. This product also includes system of adjustment of light 1-10 V and thanks to LED technology, guarantee a service life of the product 30,000 hours at 25 °C. Finishes in aluminium stylish and with a size of 88 x 86 mm, it is designed to be installed by flush mounted to ensure the total integration of the set in the space, maximizing functionalities and minimizing space.

#### APPLICATION

Ambient lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### DRIVER INCLUDED

Yes

### LUMENS/W

1000 lm/15,5W

### IP RATING

IP20

### ELECTRICAL CLASS

Type 2

### OPTICS

Wide Flood

### OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

### INTEGRATED POWER SUPPLY

No

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### POWER SUPPLY (V~)

100/240 V~

### L70 (°C)

30,000 h at 25 °C

### POWER (W)

15.5 W

### COLOR TEMPERATURE (K)

3100 K

### COLOR TYPE

WW

### POWER SUPPLY DIMENSIONS (MM)

45x141x26 mm

### CONTROL

1-10 V

### LIGHTING EFFICIENCY (LM/W)

65 lm/W

### SERVICE LIFE

30.000 h

### CRI

80

### LUMENS (LM)

1000 lm

### CHROMATICS CRI ICONS

CRI  
80

## INSTALLATION AND MAINTENANCE

### MINIMUM INSTALLATION HEIGHT

136

### INSTALLATION TYPE

Flush mount

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

## REGULATIONS

### WARRANTY

3 years 30,000 h

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.502

### PRODUCT NET WEIGHT

0.502

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053122310

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

135

### PACKAGING WIDTH

145

### PACKAGING LENGTH

155

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3.034

### PACKAGING VOLUME UNIT

DMQ

### PACKAGING GROSS WEIGHT

0.502

### PACKAGING NET WEIGHT

0.502

### PACKAGING WEIGHT UNIT

KGM