

**BNC connector 75 Ohms female with trim plate black
Simon K45**

REF. K102D/14



BASIC INFORMATION

DESCRIPTION

This connector is within the range of products Simon K45 and more specifically is a BNC 75 Ohms female connector that includes the trim plate. The product is presented in an innovative and stylish black colour that will be ideal anywhere in the, where it is. The connector installation is very simple and can be carried out by means of flush mounted or directly on the surface-mounted. The product measures 22.5 x 45 millimetres. Its clamping is carried out by welding and its type of operation is by insertion. Only have to take into account the maximum length of cabling recommended for the connector is 90 metres, if the wire is a RG-6. The connector is made of metal components with halogen-free thermoplastic insulation, which gives it great resistance and hardness, which extends its service life. Additionally, these materials are self-extinguishing, i.e. that do not contribute to of fire propagation in case of fire and reduces the toxicity of smoke, so that increases the security of the final set.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

BNC 75 Ohms female connector

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 90 metres (RG-6 cable). For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

BNC

RAL

7021

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

CONNECTOR TYPE

BNC

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

NUMBER OF CONTACTS

1

NUMBER OF WIRES

2

NUMBER OF POSSIBLE ELEMENTS

1/2 element

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.015

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046931

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.15

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.15

UNITARY PACKAGING GROSS
WEIGHT

0.015

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140