

2-wire phase-cut dimmer switch 230 V~ bronze Simon 270

REF. 20000313-097



BASIC INFORMATION

FINISH

Bronze

COMPATIBILITY

Simon 270 frames

ETIM CLASS

EC000025

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Dimmer switch and instruction sheet

REMARKS

It has a potentiometer for adjusting the minimum dimming level for the lamps.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	IP RATING IP20	OPERATING TEMPERATURE RANGE (°C) 0 - 40 °C
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	LATCH TYPE Electric	POWER SUPPLY (V~) 230 V~
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	RAL 3033
FREQUENCY 50 - 60 Hz	TYPE OF MECHANISM Pivoting	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
INDICATOR FUNCTION No		VOLTAGE (V~) 127/230 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 7	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	INSTALLATION TYPE Suitable for flush mounting
	INSTALLATION DIRECTION Horizontal	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-2-1:2004 | EN 60669-2-1:2004 A1:2009 | EN 60669-2-1:2004 A12:2010 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053282960

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.124

PRODUCT NET WEIGHT

0.124

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053282960

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

80

PACKAGING WIDTH

55

PACKAGING LENGTH

55

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

242000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.124

PACKAGING WEIGHT UNIT

KGM



Para información más detallada consultar la hoja de instrucciones
For more detailed information check the instruction sheet