

Double French socket 16 A 250V~ with safety device, light indicator and screw terminal connection red Simon Cima

REF. S2/6



BASIC INFORMATION

FINISH

Red

COMPATIBILITY

With all the enclosures of the Simon Cima range.

ETIM CLASS

EC000125

TECHNICAL INFORMATION

FORMAT

French

IP RATING

IP20

MONOBLOCK

No

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

KIT AVAILABILITY

No

RAL

3002

INDICATOR FUNCTION

Yes

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VOLTAGE (V~)

250 V~

CURRENT (A)

16 A

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

REMOVAL OF THE SOCKET

Only with tool

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436010536

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

376939

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.115

PRODUCT NET WEIGHT

0.115

UNITARY PACKAGING WEIGHT UNIT

KGM

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

118

PACKAGING WIDTH

121

PACKAGING LENGTH

264

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3769392

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.15

PACKAGING NET WEIGHT

1.15

PACKAGING WEIGHT UNIT

KGM