

Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 5e FTP white Simon K45

REF. KA95F/9



BASIC INFORMATION

DESCRIPTION

We have this plate of voice and data plate that contains a dust cover. It is suitable for one element and an RJ45 connector of category 5e FTP. this plate has a white finish and is part of the series Simon K45. The snap-fit of each plate is carried out through the Keystone I, II, ATT / Avaya. This is the individual version of the voice and data plate Simon K45, easy to install and assembly. It has four modules, and it is necessary to use the insertion tool for connection. It is available for both one or two RJ45 connectors. It is manufactured with metal components with self-extinguishing, halogen-free thermoplastic insulation. This is perfect to ensure the maximum possible security in the event of a fire. The temperatures that support these voice and data plates of the series Simon K45, can vary between -5 to the + 60 degrees centigrade. The dimensions of the plate are 45x45 mm and 42,9 millimetres of depth. To place it in vertical enclosures, it is important to take the 90 ° positioner (ref. K66). The installation of the plate requires a wire cross-section 22-24 AWG. For its correct maintenance it is only necessary to use a soft, dry cloth, of cotton and clean cloth. Do not wet the plate for cleaning.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

Four

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Flat

AVAILABLE IN

Plate with 1 and 2 RJ45 connectors

IP RATING

IP20

RAL

9003

RJ45 CONNECTION

With insertion tool

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.024

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046139

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0.24

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.12

UNITARY PACKAGING GROSS WEIGHT

0.024

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140